



ERYX 15 : Complies with environmental , health and safety standards

ERYX 15

Complies with current legislation



MERCEDES ATEGO CARRIER

Self-reliant machine, filling of the products Maintenance-free during the season. Application speed : min 3 km/h, max 25 km/h
EURO 6 engine Length: 6.25 m
Frame width: 2.25 m Weight: 11.99 t
Height: 3 m Loaded weight: 4.6 t
Manufacturer warranty: 3 years

INCREASED AUTONOMY

4.6 t to 6 t of paint or glass beads according to versions. The skids (tank and paint pumps) are interchangeable thus allowing to use either

- Water paint / Paints containing solvents
- 2-component products

APPLICATION TYPES

- New markings or maintenance ones on highways, narrow and sinuous roads, safe island edging.
- Dual strip, simultaneous marking right and left
- Pre-marking, 3-net method
- Lane moving simultaneous with the marking
- Dot and line setting
- Airport marking 45 et 90 cm-width made easier

OPTIONS

- Dual strip application
- Side-by-side guns internal and external
- Warning board with various messages
- B21 board and directional arrow
- Hand gun
- Connector for aspiration of paint under GRV
- 90 cm-ramp with quick assembly right or left
- Pre-marking, 3-net method
- Extra paint skid
- 2-component extrusion skid
- Extensive training of the truck operator
- Maintenance warranty 3 and 5 years



CONSTANT QUALITY

The quality of the marking is constantly ensured thanks to JETLINE bead guns and to the systems guarantying programmed dosings of the glass beads and paint.

DEVICE FOR THE PROTECTION OF FLEXIBLES

The chains bearing the cables allow to neatly, safely and durably carry all the hydraulic and pneumatic flexibles as well as those for paint and electric cables.

SIDE-PROTECTION DEVICES

The side-protection bars fold automatically as the marking sleighs are operated. They are UTAC-homologated under n°E2 R73 0114293 and patented n°1400420.



ERYX 15



INCREASED SAFETY AND COMFORT

- Direct eye-control on the jobsite,
- Smell-and-dust-free.
- Noise level in the cabin 63 dBA.
- Body vibration, value < à 0.3 m/s²
- Air-conditioned cabin with pollen filter
- Air-dampened seats
- Pneumatic suspensions
- Bluetooth phone
- Electric windshield curtain

Immediate and continuous operation upon arrival on, or departure from the jobsite. No stoppage, no going out on the road. Works with 2 operators, even if applying dual strip.

DIGITAL CONTROL INTERFACE

Intuitive controls gathering all functions making human errors impossible. Absolutely no calibration during the season. Getting the cruise speed of the truck is obtained by means of a single progressive control. Maintenance and defect indicator for remote trouble-shooting. Specific equipment menu:

- With or without side-by-side
- Gun selection according to the types of jobs
- P2B or P1B

DEVICE BEARING VIDEO SCREENS

The guiding screens are easily and quickly removed with a single hand avoiding to stop upon arriving at and leaving the jobsite.

VIDEO GUIDANCE

The day/night colour cameras allow an accurate guidance of the marking by an easy handling of images on each screen while applying, even if the markings are not parallel on each side.

GLASS BEAD FILLING DEVICE

A simple device allows to manoeuvre a single valve to fill in each bead tank, therefore safely ensuring the pressurization or the depressurization of the bead tanks.

PAINT PUMPS

The high-pressure AIRLESS GRACO two paint pumps are independent and allow to apply all paints on the market with different dosings, modules and line widths on the left and on the right of the truck.